



PAYLOADER



Shown With Options

**RATED
CAPACITY**

**UP TO
4,000 LBS**

**MOVE
UP TO 4
PASSENGERS**

With optional
second row seat

**RANGE
UP TO
30 MILES**

**TOW
UP TO
18,000 LBS**

Versatility is the Payloader's middle name! Choose from standard rated capacities that range from 2,400 to 4,000 lbs, and if you need to tow, the Payloader has you covered all the way up to 9 tons!

Need to carry more? Have a unique application requirement? Maintenance-free batteries, van bodies, operator cabins and folding side rails are just the beginning of a long list of available options. Let us know what you need and we'll build it!



1 Operator Cabin

2 Hydraulic Dump

3 Multiple Hitches Available






columbiavehicles.com



PAYLOADER

Dimensions

Step Height:	16.5 in / 41.91 cm
Load Bed Height:	29 in / 73.66 cm
Ground Clearance:	4.5 in / 11.43 cm



Performance

Standard Duty

Heavy Duty

Super Duty

Max Speed Forward:	13 mph	13 mph	13 mph
Turning Radius:	Curb to curb - 264 in / 670.56 cm Intersecting aisle - 92 in / 233.68 cm		
Range:	Up to 30 miles / 48.28 km		

Weight & Capacity

Vehicle Weight:	1,690 lb / 766.57 kg	1,720 lb / 780.18 kg	1,850 lb / 839.15 kg
Rated Capacity:	2,400 lb / 1088.62 kg	3,200 lb / 1451.50 kg	4,000 lb / 1814.37 kg
Towing Capacity:	6,500 lb / 2948.35 kg	10,000 lb / 4535.92 kg	18,000 lb / 8164.66 kg

Power Train

Motor:	NEMA class H temperature rated separately excited motor, optional AC		AC
Horsepower:	15.3 hp / 11.25 kW	17.3 hp / 12.72 kW	19 hp / 8 kW AC
Batteries:	Eight 6 volt, heavy duty, 232 amp hour deep cycle		
Charger:	Built-in, micro-processor control, fully sealed, anti-drive away interlock, 110-240 VAC, 50 / 60 HZ		
Controller Type:	Programmable, solid state, reduced speed reverse with diagnostic LED & calibrator interface		
Controller Rating:	400 amp DC, optional 450 AC		450 amp AC
Motor Braking Mode:	Regenerative and pedal proportional braking with top speed limiting		Regenerative braking w/top speed limiting
Directional Control:	Dash-mounted safety directional keyswitch		
Drive Unit/Differential:	Direct drive, oil bath, helical gears, 12.62:1	Direct drive, oil bath, helical gears, 16.67:1	Direct drive, oil bath, helical gears, 24.29:1

Body

Passenger Capacity:	Two with up to four (optional 2nd row seat)	Two
Seating:	Adjustable bucket seats with arm rests; second row bench seat	
Body:	Welded heavy duty; 12-gauge structural steel smooth plate body	
Lighting:	Dual recessed head; tail and brake lights	
Accessories:	Horn; battery discharge indicator; reverse warning alarm; drive seat power interlock switch; composite deck board with high density polyethylene overlay	Horn; battery discharge indicator; reverse warning alarm; drive seat power interlock switch; steel wrapped deckboard with high density polyethylene overlay

Chassis

Frame:	Heavy duty welded steel chassis with 10 gauge steel structure	Super duty has steel wrapped deck boards
Steering:	Automotive steering wheel to heavy duty worm and roller gear	
Brakes:	Dual, rear hydraulic drum, hand operated parking brake w/Interlock	4 Wheel, hydraulic brakes with front rotors, automatic parking brake
Suspension:	Independent leaf springs	
Tires:	5.70 in x 8 in / 14.48 cm x 20.32 cm, pneumatic, 8-ply rating, load range D	5.0 in x 8 in / 12.7 cm x 20.32 cm, pneumatic, 10-ply rating, load range E



BUILT FOR WORK. BACKED FOR LIFE.

No matter the job, there's a Columbia vehicle ready to take it on. Visit columbiavehicles.com to explore our full line or request a Ride & Decide today.



RIDE & DECIDE



FIND YOUR DEALER



Columbia Vehicle Group, Inc. | 2063 University Parkway, Aiken, SC 29801 | 800.222.4653 | columbiavehicles.com

©2026 Columbia Vehicle Group, Inc. LSVs are designed to comply with the United States National Highway Transportation and Safety Administration's Low Speed Vehicle rules and regulations. Operation of these vehicles is subject to all applicable state and local laws, which may limit or prohibit their lawful operation in certain environments. Do not operate these vehicles without a valid and appropriate state-issued driver's license. Inquire with the relevant authorities before attempting to operate these vehicles on roadways or in closed communities. Do not operate these vehicles in violation of applicable law, contrary to the instructions or recommendations contained in the Owner's Manual or in a manner that impedes traffic. Columbia Vehicle Group, Inc. assumes no responsibilities for any inaccuracies, opinions or omissions in this publication. All pricing, colors, specifications and features are subject to change without notice and Columbia Vehicle Group, Inc. assumes no responsibility for any such changes. Consult your authorized Columbia Vehicle Group dealer for current standard features and options. All trademarks are property of their respective owners.

COL000009 Rev 03-06-2026